

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 07.08.2012

Version: 3

Revision: 05.07.2012

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name: Wax Coating - Liquid**
- **Article number: BIG61**
- **Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**
 SU21 Consumer uses: Private households / general public / consumers
 SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Application of the substance / the preparation** Surface protection
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 Silverhook Ltd
 Bates Road, Harold Wood, London. RM3 0JH
 England
 Tel: +44(0)1708 330500
 Fax: +44(0)1708 330504
 E-mail: 333@silverhook.co.uk
- **Emergency telephone number:** During normal office hours: Tel: +44(0)1708330500

2 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.

.....



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

.....



GHS07

Acute Tox. 4 H312 Harmful in contact with skin.
 STOT SE 3 H336 May cause drowsiness or dizziness.

.....

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



N; Dangerous for the environment

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

.....

R10-66-67: Flammable. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Has a narcotizing effect.

- **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

(Contd. on page 2)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 07.08.2012

Version: 3

Revision: 05.07.2012

Trade name: Wax Coating - Liquid

(Contd. of page 1)

- **Label elements**

- **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

- **Code letter and hazard designation of product:**



N Dangerous for the environment

- **Risk phrases:**

- 10 Flammable.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

- **Safety phrases:**

- 2 Keep out of the reach of children.
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
- 39 Wear eye/face protection.
- 43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
- 46 If swallowed, seek medical advice immediately and show this container or label.

- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Substances**

- **Additional information:**

CAS: 64742-82-1 EC number: 919-446-0 Reg.nr.: 01-2119458049-33	Hydrocarbon, C9-C12, n-alkanes, iso-alkenes, cyclic, aromates(2-25%) Xn R65; N R51/53 R10-66-67 Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	25-<50%
CAS: 68608-26-4	Sodium Sulfonate Xi R36 Eye Irrit. 2, H319	2.5-<10%

- **Chemical characterization: Mixtures**

- **Description:** Mixture of waxes, additives and solvents

- **Dangerous components:** -

4 First aid measures

- **Description of first aid measures**

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.

(Contd. on page 3)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 07.08.2012

Version: 3

Revision: 05.07.2012

Trade name: Wax Coating - Liquid

(Contd. of page 2)

- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
 - Water haze
 - Fire-extinguishing powder
 - Carbon dioxide
 - Alcohol resistant foam
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mount respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:**
Observe official regulations on storing packagings with pressurized containers.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

(Contd. on page 4)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 07.08.2012

Version: 3

Revision: 05.07.2012

Trade name: Wax Coating - Liquid

(Contd. of page 3)

- **Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- **DNELs**

64742-82-1 Hydrocarbon, C9-C12, n-alkanes, iso-alkenes, cyclic, aromates(2-25%)

Oral	DNEL Long term-systemic	26 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	26 mg/kg bw/day (Consumer)
		44 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	71 mg/m ³ (Consumer)
		330 mg/m ³ (Worker)

- **Additional information:** The lists valid during the making were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:** Wash hands before breaks and at the end of work.

- **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A

- **Protection of hands:**



Protective gloves

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves** Nitrile rubber, NBR

- **Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Use protective suit.

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	142°C

- **Flash point:** 39°C

(Contd. on page 5)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 07.08.2012

Version: 3

Revision: 05.07.2012

Trade name: Wax Coating - Liquid

(Contd. of page 4)

· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	
Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	0.6 Vol %
Upper:	10.0 Vol %
· Vapour pressure at 20°C:	3.7 hPa
· Density at 20°C:	0.865 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Segregation coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	45.6 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values relevant for classification:**

64742-82-1 Hydrocarbon, C9-C12, n-alkanes, iso-alkenes, cyclic, aromates(2-25%)

Oral	LD50	>5000 mg/kg (rat)
------	------	-------------------

Dermal	LD50	>4 mg/kg (rabbit)
--------	------	-------------------

68608-26-4 Sodium Sulfonate

Oral	LD50	>6000 mg/kg (rat)
------	------	-------------------

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.

(Contd. on page 6)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 07.08.2012

Version: 3

Revision: 05.07.2012

Trade name: Wax Coating - Liquid

(Contd. of page 5)

 · **Sensitization:** No sensitizing effects known.

12 Ecological information

 · **Toxicity**

 · **Aquatic toxicity:**
64742-82-1 Hydrocarbon, C9-C12, n-alkanes, iso-alkenes, cyclic, aromates(2-25%)

EL50 (72h)	4.6-10 mg/l (Pseudokirchneriella subcapitata)
EL50(48h)	10-22 mg/l (Daphnia magna)
LL50 (96h)	10-30 mg/l (Oncorhynchus mykiss (96h))
LOEC (21 days)	0.203 mg/l (Daphnia magna)
NOEC (21 days)	0.097 mg/l (Daphnia magna)
NOELR (72h)	1 mg/l (Pseudokirchneriella subcapitata)

 · **Persistence and degradability** No further relevant information available.

 · **Behaviour in environmental systems:**

 · **Bioaccumulative potential** No further relevant information available.

 · **Mobility in soil** No further relevant information available.

 · **Ecotoxicological effects:**

 · **Remark:** Toxic for fish

 · **Additional ecological information:**

 · **General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

 · **Results of PBT and vPvB assessment**

 · **PBT:** Not applicable.

 · **vPvB:** Not applicable.

 · **Other adverse effects** No further relevant information available.

13 Disposal considerations

 · **Waste treatment methods**

 · **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

 · **Uncleaned packaging:**

 · **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

 · **UN-Number**

 · **ADR, IMDG, IATA**

UN1139

 · **UN proper shipping name**

 · **ADR**

 1139 COATING SOLUTION, mixture,
 ENVIRONMENTALLY HAZARDOUS

 · **IMDG**

COATING SOLUTION, mixture, MARINE POLLUTANT

 · **IATA**

COATING SOLUTION, mixture

(Contd. on page 7)

GB

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 07.08.2012

Version: 3

Revision: 05.07.2012

Trade name: Wax Coating - Liquid

(Contd. of page 6)

· Transport hazard class(es)

· ADR, IMDG



· Class 3 Flammable liquids.
 · Label 3

· IATA



· Class 3 Flammable liquids.
 · Label 3

· Packing group

· ADR, IMDG, IATA III

· Environmental hazards: Product contains environmentally hazardous substances: Hydrocarbon, C9-C12, n-alkanes, iso-alkenes, cyclic, aromates(2-25%)

· Marine pollutant: Yes
 Symbol (fish and tree)

· Special marking (ADR): Symbol (fish and tree)

· Special precautions for user Warning: Flammable liquids.

· Danger code (Kemler): 30

· EMS Number: F-E,S-E

· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 5L

· Transport category 3

· Tunnel restriction code D/E

· UN "Model Regulation": UN1139, COATING SOLUTION, mixture, ENVIRONMENTALLY HAZARDOUS, 3, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· National regulations:

· Technical instructions (air):

Class	Share in %
NK	25-<50

· VOC-CH 45.60 %

· VOC-EU 394.4 g/l

· Danish MAL Code 5-3

(Contd. on page 8)

GB

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 07.08.2012

Version: 3

Revision: 05.07.2012

Trade name: Wax Coating - Liquid

(Contd. of page 7)

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- R10 Flammable.
- R36 Irritating to eyes.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R65 Harmful: may cause lung damage if swallowed.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.

· **Department issuing MSDS:** Research & Development

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 ICAO: International Civil Aviation Organization
 ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)
 DNEL: Derived No-Effect Level (REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent

GB