



SILVERHOOK LTD. OIL & LUBRICANT SPECIALISTS

Unit14, Bates Road, Harold Wood, Essex, England. RM3 OJH

Switchboard: 01708 340333 Fax: 01708 340654

E-mail: 333@silverhook.co.uk Web: www.silverhook.co.uk

Technical Data Sheet

Silverhook CVT Fluid

Ref: SHCVT

Description

Silverhook CVT Fluid is formulated from premium full-synthetic base oil and is designed for most continuously variable transmissions. Its superior additive technology guards against wear & corrosion giving longer transmission life. Suitable for use in most passenger cars fitted with chain or steel belt-driven continuously variable transmissions. Silverhook CVT Fluid provides excellent cooling & low-temperature fluidity for smoother operation in cold weather.

Advantages

Enhanced friction durability for a smoother drive and longer transmission life.

Enhanced wear protection for longer transmission life.

Excellent shear thinning resistance.

Superior high temperature protection to effectively resist oxidation.

Superior variator torque capacity that can prevent belt or chain slippage.

Typical Characteristics

Relative Density @ 15C	ASTM D4052	g/ml	0.850
Kinematic Viscosity 40C	ASTM D445	mm ² /s	35
Kinematic Viscosity 100C	ASTM D445	mm ² /s	7.25
Viscosity Index	ASTM D2270	None	178
Pour Point	ASTM D97	°C	-51
Viscosity, Brookfield @ -40C	ASTM D2983	mPa.s (cP)	11100
Flash Point, COC	ASTM D92	°C	218

Product Performance

Recommended by Silverhook as suitable for use for the following specifications:

BMW Mini Cooper EZL799

Chrysler NS-2 / CVTF+4

Daihatsu AMMIX CVT Fluid DC / DFE

Dodge/Jeep Mopar CVTF+4

Ford CVT23

GM CVT/ DEX-CVT

Honda HCF-2

Hyundai/Kia SP-III

Mazda CVTF 3320

MB 236.20

MMC DIAQUEEN ATF SP-III / CVT Fluid J1/J2

Nissan CVT Fluid NS-1 / NS-2 / NS- 3

Subaru i-CVT / i-CVT FG Fluid / Lineartronic High Torque Chain CVTF

Suzuki CVT Fluid 3320 / Green / 1/2/TC/NS-2

Toyota CVT Fluid TC /FE

VAT No. GB 691 0515 44

Registered in England No. 2635167

QMS Quality
Management
Systems
BS EN ISO 9001 : 2000