

Technical Data Sheet

SILVERHOOK PETROL/INJECTOR ADDITIVE Ref: SGA02

PRODUCTS

Petrol/Injector Additive – SGA02

PRODUCT DESCRIPTION

Petrol/Injector Additive is a specially formulated after-market package to be used as regular treatment to maintain engine performance at its peak.

BENEFITS

- Will smooth out rough idling and eliminate tough starting
- Advanced corrosion protection prevents rust and fuel system blockage
- Is not harmful to catalysts
- Reduces emissions

DILUTION RATIO

325ml treats 50 to 70 litres of fuel. Maximum benefit is obtained when used at each tank fill.

PHYSICAL PROPERTIES

Properties	Method	Typical value
Appearance	Visual	Bright & Clear liquid
Density @ 15°C	ASTM D4052	0.826 kg/l
Flash point PMCC	ASTM D93	65°C
Kinematic viscosity @ 40°C	ASTM D445	2.8 cSt

HANDLING PRACTICES

Petrol/Injector Additive must be kept away from heat and sources of ignition. Always replace cap after use.

Keep away from children. Avoid release to the environment.

Avoid contact with skin and eyes. In case of accidental contact with eyes, wash thoroughly with running water for 10-15 minutes. If irritation develops and persists, seek medical advice. Wash

exposed areas of skin thoroughly with water and soap if available. If swallowed, do not induce vomiting; seek medical advice immediately and show the package label.

For more extensive information on the safe handling and use of this product, see Material Safety Data Sheet.

The content of this data sheet is given in good faith but without warranty.