

Technical Data Sheet

SILVERHOOK GREASE LITHIUM EP2 Ref: SGPG01/SGPG03/SGPG04/SGPG06/SGPG09

PRODUCTS

Silverhook Grease Lithium EP2 – SGPG01 (500g), SGPG03 (3kg), SGPG04 (12.5kg), SGPG06 (50kg), SGPG09 (180kg)

PRODUCT DESCRIPTION

A premium quality multi-purpose grease for use in all anti-friction and plain bearings subjected to high load conditions. Used extensively for applications throughout industry and the automotive sector. Approved in accordance with sheet 267.0 of Mercedes-Benz Specification for service products.

FEATURES

- Excellent extreme pressure and anti-wear performance
- High degree of corrosion protection
- Highly versatile multi purpose grease

METHOD OF APPLICATION

Silverhook Grease Lithium EP2 can be applied manually, or by using a standard grease gun (400gm cartridges available), or via a central lubricating system capable of pumping an NLGI No.2 grease. As with all greases used for the first time, check compatibility with the grease applied previously and if necessary purge bearings prior to application. Likewise, as a general rule, take care not to over-lubricate and apply the quantity of grease recommended by the bearing manufacturer.

PHYSICAL CHARACTERISTICS

Appearance	-	Smooth grease
Colour	-	Dark brown
NLGI classification	-	2
Thickener	-	Lithium soap
Base oil	-	Blend of solvent refined mineral oil
Base oil viscosity @ 40°C (IP71) cSt	-	180
Worked penetration (IP50)	-	265 to 295
Dropping point (IP132)°C	-	185 min.
Oil separation (IP121) %	-	5 max.

