

Technical Data Sheet

SILVERHOOK AUTOLUBE GREASE 000/EP Ref: SGPG34/SGPG36

PRODUCTS

Silverhook Autolube Grease 000/EP – SGPG34 (12.5kg), SGPG36 (50kg)

PRODUCT DESCRIPTION

A premium quality semi-fluid grease designed for centralised lubrication systems. Suitable for anti-friction and plain bearings subjected to high load conditions. Silverhook Autolube Grease 000/EP can also be used for gearboxes designed to operate with a semi-fluid slumping grease.

APPLICATION

Silverhook Autolube Grease 000/EP can be applied manually, or via a centralised lubricating system capable of pumping an NLGI No. 000 grease.

As with all greases used for the first time, check compatibility with the grease applied previously and if necessary purge bearings prior to application. Likewise, as a general rule, take care not to over-lubricate and apply the quantity of grease recommended by the bearing manufacturer.

BENEFITS

- Excellent extreme pressure and anti-wear performance
- High degree of corrosion protection
- Highly versatile semi-fluid grease for centralised lubrication

PHYSICAL PROPERTIES

Appearance	- Smooth semi-fluid grease
Colour	- Dark brown
NLGI Classification	- 000
Thickener	- Lithium soap
Base oil	- Blend of solvent refined mineral oil
Base oil viscosity @ 40°C (IP71) cSt	- 180
Worked penetration (IP50)	- 445 to 475
Copper corrosion (IP112)	- Pass
Resistance to corrosion Emcor (IP220)	- 0:0
Four Ball Weld Load (IP 239) kgs	- 315

VAT No. GB 691 0515 44

Registered in England No. 26351676

Timken OK Load (IP326) lbs	- 50
Operating temperature range	- -30°C to +110°C

The content of this data sheet is given in good faith but without warranty.