

Technical Data Sheet

SILVERHOOK SPRAY WHITE GREASE Ref: SGSG02

PRODUCTS

Silverhook Spray White Grease – SGSG02

PRODUCT APPLICATION

White coloured calcium enriched multipurpose grease with PTFE. Water and heat resistant lubricant, for the long term protection of bearings, axles, chains, hinges and all moving parts.

PROPERTIES

- Extreme pressure
- Anti-corrosion
- Anti-oxidation
- White coloured
- Calcium enriched
- Contains PTFE

TECHNICAL INFORMATION

Base:	Soap grease, additives
Propellant:	Propane – butane
Appearance:	White grease
Colour:	White
Pressure (@ 20°C):	4 Bar
Spray pattern:	Jet, non-dripping grease
Temperature range:	-20°C to 130°C
Dropping point:	190°C
NLGI classification:	2

DIRECTIONS FOR USE

Use on room temperature. Shake before use. Apply on the place to protect or lubricate. Let the solvents evaporate, normally this takes approximately 5 minutes. Remove excess of lubricant with a cloth. Avoid excess of lubricant.

Application temperature: 10°C – 35°C
Storage conditions: Cool (10°C – 20°C) and dry

SAFETY

See MSDS.

Keep away from heat/sparks/open flames/hot surfaces.

No smoking.

Pressurized container: Do not pierce or burn, even after use.

Do not spray on an open flame or other ignition source.

Avoid breathing spray. Wear protective gloves / eye protection. Use only outdoors or in a well-ventilated area.

The content of this data sheet is given in good faith but without warranty.