

## Technical Data Sheet

### SILVERHOOK SERVICE SPRAY WITH PTFE Ref: SGWE1

#### PRODUCTS

Silverhook Service Spray with PTFE – SGWE1

#### PRODUCT DESCRIPTION

PTFE Spray is a high quality product formulated from oils, PTFE and solvents.

#### APPLICATION

PTFE Service Spray is a product that lubricates, penetrates, protects and stops squeaking. This product is scientifically formulated for long lasting lubrication under the most severe pressure and abrasive conditions. The unique combination of synthetic lubricants and Teflon powder will form a very tough lubricating film on metal surfaces. PTFE Service Spray reduces and eliminates surface friction and wear. It penetrates inaccessible areas, repels and protects against water, moisture, salt, alkalis, acids, dirt, dust, sand, etc. PTFE Service Spray is specially developed for lubrication of parts subject to high pressure, shocks and vibrations. This product protects any moving part and prevents squeaks. The working temperature is from  $-50^{\circ}\text{C}$  up to  $+265^{\circ}\text{C}$ . PTFE Service Spray gives a transparent film.

#### DIRECTIONS FOR USE

Shake the tin well before use and spray on the area treated. Do not wipe off the excess of product immediately, because solvent will evaporate leaving a protective film. PTFE Service Spray is filled with a pollution-free gas and can be sprayed from any position.

#### SPECIFICATIONS:

|            |                |
|------------|----------------|
| Colour     | Transparent    |
| Odour      | Solvent        |
| Solvents   | Hydrocarbons   |
| Propellant | Butane/propane |

The content of this data sheet is given in good faith but without warranty.